



FLOATING
design floating floor



Embossed Wearlayer
with PU finishing
Design film
Pure PVC backing
High-density fiberboard
Cork granulate underlayment

Premium design flooring
with unique
characteristics.

FLOATING	SUPER MATTE OAK	LUNGO	LUNGO SENSES
Dimensions EN 427	1200 x 210 x 10,8mm	1800 x 220 x 10,8mm	1800 x 220 x 10,8mm
Impact Sound Reduction EN 140	18 dB	18 dB	18 dB
Emboss / Surface	Deep Wood Emboss Super-matte	Registered Emboss Semi-matte	Regular Wood Emboss Semi-matte
Class EN 430	32	33	33
Weight EN 430	11 kg/m ²	11 kg/m ²	11 kg/m ²
Dimensional Stability EN 434		0,10%	
Fire Resistance EN 131501		Bfl - S1	
Chemical Resistance EN 423		Class 0 - Good	
Abrasion Wear EN 425		Pass Castor Chair (W)	
Slippery Resistance EN 13893		DS (R9 very secure)	
Indentation EN 433		Max 0,03mm	
Anti-static Resistance EN 1815		< 2kV	
Toxicity EN 71		Non Toxic	
Resistance to Fading ISO 105 B02		6/8 depending on design	
Thermal Resistance EN 12524		0,088 m ² K/W	
AbBB/Dibt low VOC (U-Sign)		Certified	
Underfloor Heating		Approved 27°C	



AUTHENTIC LOOK



LOW VOC



RESISTANT



COMFORTABLE



ANTI-SLIPPERY



PHTHALATE FREE



EASY TO INSTALL



ANTI-STATIC



OK RADIANT HEATING



SOUND REDUCTION

UNICLIC®
EU Patent 0843 263 B1 - U.S. Patent n. 6,006,686

